



# Town Hall®



1-800-UNILOCK | [UNILOCK.COM](http://UNILOCK.COM)

**UNILOCK®**  
PAVERS & WALLS





BURGUNDY RED



BURNT CLAY



OLD OAK



BASALT



HERITAGE RED



HERITAGE CLAY



BURGUNDY RED/  
BURNT CLAY/OLD OAK  
Sold Separately/  
Blended on Site



HERITAGE  
2 COLOR BLEND  
Sold Separately/  
Blended on Site

Bundle Type	STANDARD - FULL BUNDLE	STANDARD - HALF BUNDLE
Thickness (mm)	70MM	70MM
Dimension mm	100mm x 250mm x 70mm	100mm x 250mm x 70mm
Dimension Imperial	3 7/8" x 9 7/8" x 2 3/4"	3 7/8" x 9 7/8" x 2 3/4"

SQFT PER	Bundle	88.41	44.21
	Layer	11.05000	11.05000
	Section	-	-
	Stone	0.28	0.28

PER BUNDLE	Layers	8.00	4.00
	Sections	-	-

SOLDIER LNFT PER	SqFt	1.19	1.19
	Section	-	-
	Layer	13.12	13.12
	Bundle	104.99	52.49

SAILOR LNFT PER	SqFt	2.97	2.97
	Section	-	-
	Layer	32.81	32.81
	Bundle	262.47	131.23

UNITS PER	SqFt	3.62	3.62
	Section	-	-
	Bundle	320.00	160.00

LBS PER	Layer	361	364
	Section	-	-
	Bundle	2,888	1,457



STANDARD  
9 7/8" x 3 7/8" x 2 3/4"  
250 x 100 x 70mm

## ADVANTAGES

### PERMEABLE

Can be installed to allow water to flow through

### REALA™

Cast from historic brick

### ULTIMA™

Up to 4x stronger than poured-in-place concrete

### DRIVE FRIENDLY

Can handle vehicular loads

Notes: **Sold in full and half bundles** and is produced and sold on a required, refundable skid. **Half bundles require 48 hours lead time.** **Important:** A urethane rubber paver mat must be used to prevent scuffing. For permeable installations, Unilock recommends using granite chips for joint filler. **For traditional applications, please refer to the Polymeric Sand Best Practices and Important Notice on page 83.** All measurements are nominal. Contact Unilock for more information.

Internal Use Only, TWN ON